



**INPLANA.** RADIANCE TO GET EXCITED ABOUT.

- Wide range of variants each in three sizes and the option of ceiling or wall mounting
- Room-side IP54 protection rating
- The optical system with diffuser panel and microprismatics ensures uniform, glare-free light and maximum visual comfort

[www.trilux.com/inplana](http://www.trilux.com/inplana)

Detailed product information:  
[www.trilux.com/inplana](http://www.trilux.com/inplana)



|                                                                                       |                                                                                                                                                                          |
|---------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Inplana                                                                               |                                                                                                                                                                          |
|    | <b>Mounting type</b><br>Recessed                                                                                                                                         |
|    | <b>Mounting location</b><br>Ceiling<br>Ceiling with casting box<br>Ceiling with panel system<br>System ceiling with exposed grids<br>System ceiling with concealed grids |
|  | <b>Design</b><br>round                                                                                                                                                   |
|  | <b>Sizes</b><br>215 mm, 300 mm, 425 mm                                                                                                                                   |
|  | <b>Beam characteristic</b><br>wide                                                                                                                                       |
|  | <b>Luminaire luminous flux</b><br>1,000 - 5,000 lm                                                                                                                       |
|  | <b>Colour rendering index   Light colour</b><br>Ra > 80<br>3,000 K<br>4,000 K<br>Tunable White 2,700 K – 6,500 K                                                         |
|  | <b>Service life</b><br>L85 = 50,000 h<br>L80 = 70,000 h                                                                                                                  |
|  | <b>Luminaire colour</b><br>white                                                                                                                                         |
|  | <b>Operating mode</b><br>switchable and DALI dimmable (ETDD)<br>Bluetooth Low Energy (ETBLE)<br>switchable (ET)                                                          |
|  | <b>Connectivity</b><br>Casambi capable                                                                                                                                   |
|  | <b>Additional equipment</b><br>Single battery system, 3 hours                                                                                                            |
|  | <b>Accessories</b><br>Concrete casting box<br>Mounting cases for panel ceilings<br>Recessing frame<br>Mounting plates                                                    |



Unique optic for maximum visual comfort

# CONTACTS

## **TRILUX GmbH & Co. KG**

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

[www.trilux.com/en](http://www.trilux.com/en)

## **SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.**

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

[www.endalight.com](http://www.endalight.com)

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.