

TOKO. THE MULTI-FACETED DOWNLIGHT.

- Powerful LED downlights for clear, fresh lighting even in high rooms
- Available in two sizes with luminous fluxes from 2,000 lm to 7,000 lm
- 3D faceted reflectors with four beam angles [28°, 38°, 48°, 60°] for flexible lighting from uniform to accentuated
- The intelligent fixing method enables quick, easy and economical mounting
- Suitable for smart light management, either with control line or wireless
- The compact design with mounting rings in black, white or silver blends discreetly into all surroundings

www.trilux.com/toko
www.trilux.com/toko-plus

Detailed product information:
www.trilux.com/toko
www.trilux.com/toko-plus



Toko Toko Plus

Mounting type
Recessed

Functions
General lighting
Accent lighting

Light point height
2.8 - 4.5 m

Beam characteristic
medium flood
flood
wide flood
very wide flood

Luminaire luminous flux
2,000 lm - 5,000 lm (Toko)
3,000 lm - 7,000 lm (Toko Plus)

Colour rendering index | Light colour
Ra > 80
2,700 K
3,000 K
3,500 K
4,000 K
Ra > 90
2,700 K - Brilliant Food (BF)
3,100 K - Brilliant Colour (BC)
3,200 K - Efficient White (EW)
4,000 K - Efficient Cool (EC)

Service life
L80 = 50,000 h

Luminaire colour
black
silver-grey
white

Operating mode
switchable and DALI dimmable (ETDD)
Bluetooth Low Energy (ETBLE)
switchable (ET)

Connectivity
Casambi capable



TOKO

DOWNLIGHTS



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.