


665. AS SIMPLE AS ALWAYS.
MORE EFFICIENT THAN EVER
BEFORE.

- Optimally designed to meet the requirements of standard sanitary applications – from IP rating to luminaire dimensions
- Length-optimised for tile and mirror dimensions
- Functional design with flat end caps


www.trilux.com/665

Detailed product information:
www.trilux.com/665



665

WALL AND CEILING LUMINAIRE



665

 **Mounting type**
Surface-mounted

 **Mounting location**
Wall

 **Beam characteristic**
Lambertian

 **Luminaire luminous flux**
1,100 - 2,400 lm

 **Colour rendering index | Light colour**
Ra > 80
3,000 K
4,000 K

 **Service life**
L80 = 50,000 h

 **Luminaire colour**
white
chrome

 **Operating mode**
switchable (ET)

    IP40

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.