











- and emergency light
- Seamless light emission surface with the continuous-line version
- Flexibly positionable wire suspension for simple refurbishment

www.trilux.com/luceos-led

Luceos H



& Mounting location Ceiling

Size

A Beam characteristic

wide direct-indirect wallwasher

O Luminaire luminous flux 4,000 - 8,400 lm

🔅 Colour rendering index | Light colour Ra > 80

3,000 K 4,000 K

Tunable White 2,700 K – 6,500 K

① Service life L90 = 50.000 h

C Luminaire colour silver-grey

white

ψ Operating mode

switchable and DALI dimmable (ETDD)

((†)) Connectivity

LiveLink capable Casambi capable

Additional equipment
LiveLink sensor IR Micro for daylightdependent control and presence detection Single battery system, 3 hours CO_2 sensor to indicate air quality and need for ventilation

Accessories

Ceiling roses Ceiling roses with LiveLink Nodes Node couplings End caps without function End caps with supplementary function Continuous-line couplings Continuous-line couplings with supplementary function Wire suspensions Connection cables



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg
Postfach 19 60 • D-59753 Arnsberg
GERMANY
Tel. +49 2932 301-0
www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18 34775 Ümraniye Istanbul TURKEY

Tel: +90 (216) 499 46 64 www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.

www.trilux.com 252-GB-int. 104 295 43