



4401. BRINGS METAL STRIP CEILINGS INTO THE FUTURE.

- Customised luminaire lengths, mounting concepts and lighting technologies specifically for metal strip ceilings make refurbishments simple and straightforward
- The 4401 G2 enables efficient 1:1 refurbishment of conventional luminaires in corridors, changing rooms, sanitary areas and canopied outdoor areas
- The 4401 G2 is particularly attractive economically due to its high efficiency, maintenance-friendly design and long service life

www.trilux.com/4401

Detailed product information:
www.trilux.com/4401



4401	
	Mounting type Recessed
	Mounting location Ceiling
	Beam characteristic wide
	Luminaire luminous flux 1,000 - 4,000 lm
	Colour rendering index Light colour Ra > 80 3,000 K 4,000 K
	Service life L80 = 60,000 h
	Luminaire colour white
	Operating mode switchable and DALI dimmable (ETDD) switchable (ET)
	Additional equipment Single battery system, 3 hours Switching relay for emergency power supply systems
	Accessories Removal tool Fixing accessories Spare parts Replacement diffusers

   IP54

4401

RECESSED LUMINAIRES



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.