



ACQUEX. THE STRONG EX SOLUTION FOR A SAFE START.

- Acquex is a robust entry-level solution for ATEX zones 2/22
- Ex-certified components, Ex standard-compliant mounting and the technical concept of the luminaire guarantee protection for industrial ATEX zones
- Can be optionally mounted as a wall or ceiling luminaire and features simple and safe installation (Ex cable gland)
- High impact resistance (IK10), up to 8,000 lm, versions available with DALI and emergency light battery
- Long life cycles of up to 100,000 hours and therefore maximum savings in terms of maintenance costs

www.trilux.com/atex

Detailed product information:
www.trilux.com/atex



Acquex	
	ATEX designation Gas: II 3G Ex ec IIC T6 Gc Dust: II 3D Ex tc IIIC T85°C Dc
	Mounting type Surface-mounted
	Mounting location Ceiling Wall Outdoor ceiling
	Beam characteristic lambertian
	Luminaire luminous flux 2,000 - 8,000 lm
	Colour rendering index Light colour Ra > 80 3,000 K 4,000 K
	Service life L80 = 70,000 h
	Luminaire colour signal yellow
	Operating mode switchable and DALI dimmable (ETDD) switchable (ET)
	Additional equipment Single battery system, 3 hours
	Accessories Steel strip suspensions

  IP66

ACQUEX

LUMINAIRES WITH HIGHER PROTECTION RATING



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.