



# NEXTREMA G3. THE TOUGH WEATHER-PROOF LUMINAIRE FOR EXTREME SITUATIONS.

- High efficiency (HE) versions with up to 170 lm/W and with up to 100,000 hours with extremely low maintenance. Costly idle times during running operation in production halls become a thing of the past
- Thanks to high-quality workmanship, a robust die-cast aluminium body and an impact-resistant concept, Nextrema G3 withstands moisture, dirt and temperature deviations of -40° to 50°C

#### Nextrema G3

# **№** Mounting type

Surface-mounted Suspended

## ▲ Mounting location

Ceiling
Wall
Outdoor wall, canopied
Outdoor ceiling
Outdoor, not canopied (PMMA)

# $\overline{\underline{\mathbb{A}}}$ Beam characteristic

wide extremely wide narrow-wide asymmetric

# Q Luminaire luminous flux 2,300 - 12,500 lm

#### -☆ Colour rendering index | Light colour Ra > 80 4,000 K

# Service life L80 = 100,000 h

C Luminaire colour

# anthracite

 ♥ Operating mode switchable and DALI dimmable (ETDD) switchable (ET)

## ((j)) Connectivity

LiveLink integrated Monitoring Ready CLO ready Swarm intelligence

#### 🌣 Additional equipment

Phönix quick-connect system Wieland quick-connect system Through-wiring Motion sensor HCL optional

#### Accessories

Theft protection Emergency luminaires Sensor remote control Steel strip suspensions Wall holder





# **CONTACTS**

#### TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg
Postfach 19 60 • D-59753 Arnsberg
GERMANY
Tel. +49 2932 301-0
www.trilux.com/en

#### SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18 34775 Ümraniye Istanbul TURKEY

Tel: +90 (216) 499 46 64 www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.

www.trilux.com 252-GB-int. 104 295 43