







OLEVEON FIT. SIMPLY PLANNED. FLEXIBLY REFURBISHED. FIT FOR THE FUTURE.

- Ideal refurbishment solution for simple 1:1 replacements due to extensive portfolio including DALI, sensor and
- High-quality light and low operating costs thanks to 3D prismatic technology and energy efficiency of up to
- Wide range of variants for customised lighting concepts
- Future-proof due to intelligent connectivity features and
- Further customising during installation via multilumen variants

www.trilux.com/oleveon-fit-led

Oleveon Fit

Suspended Surface-mounted

& Mounting location

Wall Ceiling Outdoor wall, canopied Outdoor ceiling

👼 Beam characteristic

wide lambertian

O Luminaire luminous flux

1,750 - 7,900 lm

⊙ Colour rendering index | Light colour

Ra > 80 4,000 K 6,500 K

Service life

L80 = 50,000 h

C Luminaire colour

light grey transparent green

◆ Operating mode

switchable and DALI dimmable (ETDD) switchable (ET)

(ין) Connectivity
LiveLink integrated Monitoring Ready CLO ready LiveLink WiFi

♦ Additional equipment

HCL optional Motion sensor Through-wiring Single battery system, 3 hours Multilumen option
ADELS quick-connect system

Accessories

Theft protection Sensor remote control Steel strip suspensions . Wall holder Through-wiring Replacement diffusers



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg
Postfach 19 60 • D-59753 Arnsberg
GERMANY
Tel. +49 2932 301-0
www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18 34775 Ümraniye Istanbul TURKEY

Tel: +90 (216) 499 46 64 www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.

www.trilux.com 252-GB-int. 104 295 43