



STRONGEX G2. EXTREMELY ROBUST AND CHEMICALLY RESISTANT EX TUBULAR LUMINAIRE.

- Thanks to an extremely robust design and gas-tight seal, Strongex G2 withstands impacts (IP69K) as well as aggressive gases, acids and salty atmospheres.
- The luminaire is made of highly impact-resistant PMMA and the end caps of PA66 and glass fibre. The DALI-dimmable solution is certified for ATEX zones 2, 22 and 1, 21.
- Long life cycles of up to 100,000 hours and therefore maximum savings in terms of maintenance costs
- Extremely efficient luminaire with up to 182 lm/W and use in ambient temperatures from -36°C to +55°C.

www.trilux.com/atex

Detailed product information:
www.trilux.com/atex



Strongex G2	
	ATEX designation STRONGEX 1 G2 [S1] Gas: II 2G Ex eb mb IIC T4 Gb Dust: II 2D Ex tb IIIC T85°C Db STRONGEX 2 G2 [S2] Gas: II 3G Ex ec IIC T6 Gc Dust: II 3D Ex tc IIIC T85°C Dc
	Mounting type Surface-mounted
	Mounting location Ceiling Wall Outdoor ceiling Outdoor wall
	Beam characteristic wide
	Luminaire luminous flux 2,800 - 8,500 lm
	Colour rendering index Light colour Ra > 80 4,000 K
	Service life L80 = 100,000 h
	Luminaire colour signal yellow
	Operating mode switchable and DALI dimmable (ETDD) switchable (ET)
	Additional equipment Through-wiring
	Accessories Connection accessory Wiring connectors
  IP66	

STRONGEX G2

LUMINAIRES WITH HIGHER PROTECTION RATING



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.