



8841. POWERFUL WITH STYLE AND SMART FUNCTIONS.

- Thanks to its classic design, 8841 blends harmoniously into the building environment and sets visual accents
- The multi-lens technology (MLT[®]) guarantees standard-compliant illumination even at wide light point spacing of up to 14 metres
- Smart additional functions in the supporting column
- With versions with 180° shading, the proportion of light emitted to the rear is 0 %

www.trilux.com/8841

Detailed product information:
www.trilux.com/8841



8841	
	Mounting type Outdoor free-standing mounting
	Mounting location Outdoor ground
	Beam characteristic asymmetric wide rotationally symmetric wide
	Luminaire luminous flux 700 - 850 lm
	Colour rendering index Light colour Ra > 70 3,000 K 4,000 K
	Service life L80 = 100,000 h
	Luminaire colour anthracite
	Operating mode switchable and DALI dimmable (ETDD)
	Additional equipment PIR sensors
	Accessories Underground supports Underground support with continuous supporting column Supporting column with socket Supporting column with sensor

CE UK IP65

8841

BOLLARD LUMINAIRES



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.