



JOVIE

FLEXIBLE, ATTRACTIVE AND FIT FOR THE FUTURE.

- 100% Dark Sky – sustainable and ecological outdoor lighting for a starry sky without light pollution
- Future-proof – Smart Lighting Ready (SLR) variant with up to two Zhaga-standardised sockets for light management system and sensors
- Attractive – customisable cover
- Configurable

Detailed product information:
www.trilux.com/jovie



JOVIE

Mounting type
Bracket-mounted
Post-top-mounted
Surface-mounted

Light point height
3 - 8 m
6 - 14 m

Mounting location
Outdoor posts
Outdoor wall

Design
small (Jovie 50)
large (Jovie 70)

Beam characteristic
asymmetric wide
symmetric wide

Luminaire luminous flux
1,000 - 24,000 lm

Colour rendering index | Light colour
Ra > 70
2,200 K
2,700 K
3,000 K
4,000 K

Service life
L80 = 100,000 h

Luminaire colour
anthracite

Operating mode
switchable and DALI dimmable (ETDD)
switchable (ET)

Additional equipment
Power reduction, control phase (LR)
Multilumen (ML)
Constant Light Output (CLO)

Accessories
Shieldings
Junction boxes
Post mounting elements
Post mounting
Mounting accessories
Reduction pieces
Wall mountings



JOVIE

POST LUMINAIRES



JOVIE CONFIGURATOR
PLAN QUICKLY AND EASILY NOW!



GET IT DONE IN JUST A FEW STEPS



Start the customised configuration!

STEPS	SELECTION OPTIONS	
Size	2	Jovie 50, Jovie 70
Light distribution	8	AB2L AB5L AB7L FR1L FL1L SB3L AM2L AM3L
Luminous flux	Jovie 50: 1,000 lm ... 6,800 lm	
	Jovie 70: 6,800 lm ... 24,000 lm	
	Multilumen: 1,000 - 2,200 lm 1,650 - 4,200 lm 4,600 - 6,800 lm 7,500 - 15,000 lm 16,500 - 24,000 lm	
Light colour / CRI	4	2,200 K 2,700 K 3,000 K 4,000 K CRI70
Switching type	7	LR LRA ET ETDD SLR1 SLR2 SLR3
Colour	7	DB703 DB702 DB701 RAL9006 RAL 9005 RAL7043 RAL7035
Connection cable length	6	6 m 8 m 10 m 12 m 14 m 16 m
Connection cable UV-resistant	2	Standard connection cable (NYM), UV-resistant silicone connection cable

Ready! After configuration, all data can be directly downloaded.

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.