

COMBIAL G2. A ROBUST FLOODLIGHT FOR THE PRICE-CONSCIOUS.

- Entry product with an attractive price and familiar TRILUX quality
- The LED floodlight version with 12,000 lm replaces a 150 watt floodlight one-to-one
- Safety class I and an IP65 protection rating for high robustness

www.trilux.com/combial

Detailed product information:
www.trilux.com/combial



Combial G2

Mounting type
Outdoor post-top mounting
Outdoor directional mounting
Surface-mounted

Mounting location
Outdoor ceiling
Outdoor wall
Outdoor ground
Outdoor posts

Beam characteristic
rotationally symmetric wide
asymmetric medium-wide

Luminaire luminous flux
1,850 - 32,500 lm

Colour rendering index | Light colour
Ra > 80
3,000 K
4,000 K
Multicolour

Service life
L80 = 50,000 h

Luminaire colour
black

Operating mode
switchable (ET)

Accessories
Sensors

CE UK IP65

COMBIAL G2

FLOODLIGHTS



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.