







Outdoor post-top mounting Outdoor directional mounting Outdoor surface-mounting

Mounting location
Outdoor ground
Outdoor posts Outdoor wall

Beam characteristic

asymmetric wide asymmetric medium-wide asymmetric narrow

C Luminaire luminous flux 2,200 - 200,000 lm

Colour rendering index | Light colour Ra > 70

2,200 K 2,700 K 3,000 K 4,000 K

Service life
 L80 = 100,000 h

C Luminaire colour

anthracite

♥ Operating mode switchable and DALI dimmable (ETDD) switchable and dimmable (DMX)

('[')) Connectivity
Smart Lighting Ready (SLR)

♦ Additional equipment

Power reduction, control phase (LR)

Accessories

Mounting accessories Cross-arms Wall mountings





FLEXIBLE LIGHTING OF INDUSTRIAL FACILITIES.

- Lumena Plus is completely pre-assembled and can be mounted on walls and ceilings without further accessories. This saves time and costs and makes Lumena Plus particularly user-friendly and flexible to install
- Lumena Plus is officially certified by IDA Dark Sky
- Sustainability that remains economical: the increased energy efficiency minimises energy consumption and greenhouse gas emissions – reliably and in the long run

www.trilux.com/lumena-plus

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg
Postfach 19 60 • D-59753 Arnsberg
GERMANY
Tel. +49 2932 301-0
www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18 34775 Ümraniye Istanbul TURKEY

Tel: +90 (216) 499 46 64 www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.

www.trilux.com 252-GB-int. 104 295 43