FLOODLIGHTS







Lumena Star 40

✗ Mounting type

Outdoor post-top mounting Outdoor directional mounting Surface-mounted

$\stackrel{\&}{ ext{$\triangle$}}$ Mounting location

Outdoor ceiling Outdoor wall Outdoor ground Outdoor posts

🚡 Beam characteristic

rotationally symmetric wide rotationally symmetric narrow

Q Luminaire luminous flux 2,200 - 10,000 lm

- ; Colour rendering index | Light colour Ra > 70 4,000 K

Service life L80 = 100,000 h

C Luminaire colour silver-grey

Operating mode switchable (ET)

• Accessories Shieldings Post connections Post straps Cross-arms

蛋(€ 點 🏝 🕒 1P66

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg
Postfach 19 60 • D-59753 Arnsberg
GERMANY
Tel. +49 2932 301-0
www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18 34775 Ümraniye Istanbul TURKEY

Tel: +90 (216) 499 46 64 www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.

www.trilux.com 252-GB-int. 104 295 43