



LINELL. CONVINCING ALL ALONG THE LINE.

- Flush-mounted linear inserts: inserts with opal cover, lens optic or wallwasher optic are flush with the track
- Opal optic for precise lines of light in the room
- With UGR 19, the lens optic meets the requirements for standard-compliant lighting in offices
- The wallwasher optic is ideal for displaying vertical objects
- Available in three lengths: 500 mm, 1,000 mm, 1,500 mm

www.trilux.com/linell



Detailed product information:
www.trilux.com/linell



Linell	
 Mounting type	Track
 Functions	Accent lighting General lighting
 Light point height	up to 3.5 m
 Beam characteristic	lamertian flood very wide flood wallwasher
 Luminaire luminous flux	950 lm – 3,500 lm
 Colour rendering index Light colour	Ra > 80, Ra > 90 2,700 K 3,000 K 4,000 K
 Service life	L80 = 50,000 h
 Luminaire colour	black white
 Operating mode	switchable and DALI dimmable (ETDD)
    IP20	

LINELL

RAIL TRACK SYSTEM (STUCCHI)



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.