





✗ Mounting type

Recessed

& Mounting location

System ceiling with exposed grids System ceiling with concealed grids Ceiling Ceiling with panel system

🕮 Design

square linear

🚡 Beam characteristic

wide (also in UGR < 16) wallwasher

Q Luminaire luminous flux 3,000 - 7,000 lm

Octoour rendering index | Light colour Ra > 80, Ra > 90

3,000 K 4,000 K Tunable White 2,700 K – 6,500 K

① Service life

L90 = 50,000 h L80 = 100,000 h

C Luminaire colour

white with anthracite limiter white with white limiter white with black limiter

♥ Operating mode

switchable and DALI dimmable (ETDD)
Bluetooth Low Energy (ETBLE)
switchable (ET)

((†)) Connectivity

LiveLink integrated Casambi integrated

🗘 Additional equipment

Linect® quick-connect system LiveLink sensor IR Micro for daylightdependent control and presence detection Single battery system, 3 hours Beacon for location-based services

Accessories

Mounting accessories Diffuser removal tool











- High efficiency and quality of light with ConVision® technology
- Light chambers in three different colours for different lighting effects without influencing the light distribution curve and customisation on request
- High-quality material and excellent workmanship such as sheet steel body

www.trilux.com/creavo-led

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg
Postfach 19 60 • D-59753 Arnsberg
GERMANY
Tel. +49 2932 301-0
www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18 34775 Ümraniye Istanbul TURKEY

Tel: +90 (216) 499 46 64 www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.

www.trilux.com 252-GB-int. 104 295 43