



OPENDO C. ADVANCED LIGHTING.

- High-quality planar light for education and offices
- Rapid refurbishment of old conventional linear luminaires
- Variants with integrated daylight and presence control or emergency light function
- Easy retroactive removal of the control gear unit if required

www.trilux.com/opendo-led

Detailed product information:
www.trilux.com/opendo-led



Opendo C	
	Mounting type Recessed
	Mounting location System ceiling with exposed grids System ceiling with concealed grids Ceiling Ceiling with panel system
	Design linear
	Beam characteristic wide
	Luminaire luminous flux 3,400 - 4,700 lm
	Colour rendering index Light colour Ra > 80 3,000 K 4,000 K Tunable White 2,700 K – 6,500 K Further light colours on request
	Service life L80 = 50,000 h
	Luminaire colour white
	Operating mode switchable and DALI dimmable (ETDD) Bluetooth Low Energy (ETBLE) switchable (ET)
	Connectivity LiveLink integrated Casambi integrated
	Additional equipment LiveLink sensor IR Micro for daylight-dependent control and presence detection Single battery system, 3 hours Switching relay for emergency power supply systems
	Accessories Mounting accessories Spare parts Diffuser removal tool

    IP20



OPENDO C

RECESSED LUMINAIRES

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.