

NORDIC TRACK SYSTEM











Yuvio Track Yuvio Twin

Mounting type

Track

✓ Functions

General lighting Accent lighting Aisle zone lighting

The Light point height 2.8 - 4.5 m

🚡 Beam characteristic

Yuvio Track super spot spot medium flood flood oval Yuvio Twin

Luminaire luminous flux

1,500 lm - 5,000 lm (Yuvio Track) $2 \times 2,000 \text{ lm} - 2 \times 5,000 \text{ lm}$ (Yuvio Twin)

∵o Colour rendering index | Light colour

Yuvio Track 2,700 K 3,000 K 3,500 K 4,000 K Ra > 90 2,700 K - Brilliant Food (BF) 3,100 K - Brilliant Colour (BC) 3,200 K - Efficient White (EW) 4,000 K - Efficient Cool (EC) Meat (M) Meat + Fish (M+F) Yuvio Twin Ra > 80 2,700 K 3,000 K 3,500 K 4,000 K 3,200 K - Efficient White (EW) 4,000 K - Efficient Cool (EC)

Service life

L80 = 50,000 h

○ Luminaire colour

black silver-grey white

♥ Operating mode

switchable and DALI dimmable (ETDD)
Bluetooth Low Energy (ETBLE) switchable (ET)

((j)) Connectivity

Casambi capable





CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg
Postfach 19 60 • D-59753 Arnsberg
GERMANY
Tel. +49 2932 301-0
www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18 34775 Ümraniye Istanbul TURKEY

Tel: +90 (216) 499 46 64 www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.

www.trilux.com 252-GB-int. 104 295 43