







Mounting type

Surface-mounted

$\stackrel{Q}{ ... } {\bf Mounting \ location}$

Ceiling

🕮 Design square linear

🚡 Beam characteristic wide (also in UGR16) wallwasher

Q Luminaire luminous flux 3,000 - 7,000 lm

🤅 Colour rendering index | Light colour Ra > 80, Ra > 90 3,000 K 4,000 K Tunable White 2,700 K - 6,500 K

Service life L90 = 50,000 hL80 = 100,000 h

C Luminaire colour white with anthracite limiter white with white limiter white with black limiter

Uperating mode switchable and DALI dimmable (ETDD) switchable (ET)

((j)) Connectivity LiveLink integrated Casambi capable

Additional equipment
LiveLink sensor IR Micro for daylightdependent control and presence detection

Single battery system, 3 hours Beacon for location-based services

Accessories End caps without function Continuous-line couplings Through-wiring









CREAVO D. THE FUTURE-ORIENTED LIGHT.

- ConVision® technology for high efficiency and quality of light
- Light chambers in three different colours for different lighting effects without influencing the light distribution curve and customisation on request $% \left(1\right) =\left(1\right) \left(1\right) \left($
- High-quality material and excellent workmanship such as sheet steel body

www.trilux.com/creavo-led

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg
Postfach 19 60 • D-59753 Arnsberg
GERMANY
Tel. +49 2932 301-0
www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18 34775 Ümraniye Istanbul TURKEY

Tel: +90 (216) 499 46 64 www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.

www.trilux.com 252-GB-int. 104 295 43