



JUNO. PURE LIGHT JEWEL.

- Suspended luminaires as all-rounders for complete shop lighting
- An outstanding feature: the drop-shaped free-form lens with oval light distribution
- Avant-garde design and winner of the Red Dot Design Award 2020
- Suitable for smart light management: optionally with control line or wireless
- Suspended luminaires for recessing, surface-mounting or track mounting, with pendant length adjustable from 0.1 to 1.5 metres or 1.5 to 3 metres

www.trilux.com/juno



Detailed product information:
www.trilux.com/juno



Juno

	Mounting type Track Suspended
	Functions Decorative lighting
	Light point height 2.8 - 4.5 m
	Beam characteristic oval
	Luminaire luminous flux 2,000 lm - 4,000 lm
	Colour rendering index Light colour Ra > 80 2,700 K 3,000 K 4,000 K Ra > 90 3,200 K - Efficient White (EW) 4,000 K - Efficient Cool (EC)
	Service life L80 = 50,000 h
	Luminaire colour black white
	Operating mode switchable and DALI dimmable (ETDD) Bluetooth Low Energy (ETBLE) switchable (ET)
	Connectivity Casambi capable

CE UK IP20



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.