





№ Mounting type

Track Suspended

▼ FunctionsGeneral lighting
Decorative lighting

Light point height 2.8 - 4.5 m

Beam characteristic lambertian

Q Luminaire luminous flux

2,000 lm

∴ Colour rendering index | Light colour
Ra > 80
3,000 K
4,000 K
Tunable White


Service life L80 = 50,000 h

C Luminaire colour black white

 ♥ Operating mode switchable and DALI dimmable (ETDD) Bluetooth Low Energy (ETBLE)

(1) Connectivity
Casambi capable

C € ĽK ⊕ � IP20 🎄



Also available for Rail (Stucchi) and Nordic.

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg
Postfach 19 60 • D-59753 Arnsberg
GERMANY
Tel. +49 2932 301-0
www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18 34775 Ümraniye Istanbul TURKEY

Tel: +90 (216) 499 46 64 www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.

www.trilux.com 252-GB-int. 104 295 43