MIRONA FIT SPORT

BALL-PROOF LUMINAIRES





Suspended Surface-mounted

Ceiling Wall

A Beam characteristic

Colour rendering index | Light colour Ra > 80

① Service life L80 (tq 50 °C) = 100,000 h

white

♥ Operating mode switchable and DALI dimmable (ETDD)

(יןי) Connectivity Monitoring Ready

Fixing bracket Wall mountings Chain suspensions

壓 (€ 以 ⊕ IP65 🎄



- Reinforced housing concept for ball-impact resistance in sports halls
- Reliability, low maintenance and long 100,000 hour service life

www.trilux.com/mirona-fit-led


zeefdruk gerjo

belettering zeefdruk gerjo











Ra > 90 4,000 K

C Luminaire colour



Accessories



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg
Postfach 19 60 • D-59753 Arnsberg
GERMANY
Tel. +49 2932 301-0
www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18 34775 Ümraniye Istanbul TURKEY

Tel: +90 (216) 499 46 64 www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.

www.trilux.com 252-GB-int. 104 295 43