



WALL AND CEILING LUMINAIRES







Mounting type

🚨 Mounting location ${\tt Outdoor\,wall}$

Outdoor ceiling

lambertian

900 - 2,000 lm

· . Colour rendering index | Light colour Ra > 80 3,000 K 4,000 K

Service life L80 = 100,000 h

anthracite white

🗘 Additional equipment

Motion sensor Multilumen Multicolour

Accessories

(€ KK 🕀 IP65

SKEO CIRC. A WELL-ROUNDED AFFAIR FOR AREAS AROUND

• An attractive and robust outdoor luminaire for areas


• Luminous flux and light colour can also be very simply set after mounting via a switch in the luminaire

www.trilux.com/skeocirc

• A classic round design and high quality of light • Economical due to high energy efficiency and long

BUILDINGS.

around buildings



👼 Beam characteristic

Luminaire luminous flux

○ Luminaire colour





CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg
Postfach 19 60 • D-59753 Arnsberg
GERMANY
Tel. +49 2932 301-0
www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18 34775 Ümraniye Istanbul TURKEY

Tel: +90 (216) 499 46 64 www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.

www.trilux.com 252-GB-int. 104 295 43