

SKEO R. A LIGHT COMPONENT FOR STRIKING BUILDING AND PATH LIGHTING.

- Wide design scope meeting the most diverse lighting requirements thanks to various lumen packages
- Numerous distribution characteristics, two different sizes and single or double light emission
- Purist design blends into the surroundings
- High-quality die-cast aluminium housing makes the luminaire resistant against environmental and weather factors

www.trilux.com/skeor

Detailed product information:
www.trilux.com/skeor



Frosted or transparent glass



Variety of distribution characteristics

Skeo R

Mounting type
Surface-mounted

Mounting location
Outdoor wall
Outdoor ceiling

Beam characteristic
asymmetric wide
symmetric narrow

Luminaire luminous flux
600 - 4,000 lm

Colour rendering index | Light colour
Ra > 70
3,000 K

Service life
L80 = 50,000 h

Luminaire colour
anthracite

Operating mode
switchable (ET)

CE UK IP65

CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.