




FACIELLA. ONE SPOTLIGHT. THREE SIZES.
ALL POSSIBILITIES.

- Available in three sizes, the high-performance, energy-efficient Faciella spotlight displays objects, surfaces and buildings of various types and sizes in a uniform design
- Various luminous flux packages and beam angles provide suitability for a variety of lighting tasks, enabling customised light
- Supply includes the luminaire cable ready for connection – the luminaire must not be opened during mounting, thus simplifying and accelerating installation

www.trilux.com/faciella

Detailed product information:
www.trilux.com/faciella




Faciella	
	Mounting type Outdoor post-mounting Outdoor directional mounting
	Mounting location Ground Ceiling Wall Outdoor ground Outdoor wall Outdoor wall, canopied
	Beam characteristic rotationally symmetric narrow rotationally symmetric wide rotationally symmetric medium wide
	Luminaire luminous flux 120 - 4,200 lm
	Colour rendering index Light colour Ra > 80 3,000 K 4,000 K amber blue green red
	Service life L80 = 50,000 h
	Luminaire colour anthracite
	Operating mode switchable (ET)
	Accessories Shields Ground stakes Filters Post connections Post straps

CE UK IP65



FACIELLA

SPOTLIGHTS



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.