



SKEO Q-S. POSSIBILITIES SQUARED AROUND BUILDINGS.

- With their linear design, the luminaires blend perfectly into the building environment and set attractive accents
- Reliably resist even harsh weather conditions thanks to high-quality die-cast aluminium luminaire housing and IP65
- A functional family of luminaires makes it possible to illuminate the entire area around the building in a uniform design

www.trilux.com/skeoqs

Detailed product information:
www.trilux.com/skeoqs




Skeo Q-S	
	Mounting type Outdoor directional mounting
	Mounting location Ground Ceiling Wall Outdoor ground Outdoor wall Outdoor wall, canopied
	Beam characteristic rotationally symmetric narrow rotationally symmetric wide rotationally symmetric medium wide
	Luminaire luminous flux 450 lm
	Colour rendering index Light colour Ra > 70 3,000 K 4,000 K
	Service life L80 = 50,000 h
	Luminaire colour anthracite
	Operating mode switchable (ET)

CE UK IP65

SKEO Q-S

SPOTLIGHTS



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.