



98... A SYMBIOSIS OF DESIGN AND FUNCTION.

- Customised light thanks to Multi-Lens Technology (MLT[®]): a diversity of versions for the systematic illumination of roads and squares
- Rapid, simple mounting, a long service life and longer maintenance cycles with minimal maintenance effort
- E-block inserted and replaced without tools

www.trilux.com/981
www.trilux.com/982
www.trilux.com/983
www.trilux.com/985
www.trilux.com/986
www.trilux.com/987

Detailed product information:
www.trilux.com/981
www.trilux.com/982
www.trilux.com/983
www.trilux.com/985
www.trilux.com/986
www.trilux.com/987



98...

	Mounting type Post-top-mounted Surface-mounted
	Light point height 3 - 6 m
	Mounting location Outdoor posts Outdoor wall
	Design Lantern Decorative indirect lantern Conical Classic Classic conical Classic mushroom
	Beam characteristic asymmetric wide rotationally symmetric wide
	Luminaire luminous flux 1,200 - 3,800 lm
	Colour rendering index Light colour Ra > 70, Ra > 80 3,000 K 4,000 K
	Service life L80 = 100,000 h (MLT [®]) L80 = 50,000 h (secondary optic)
	Luminaire colour black
	Operating mode switchable (ET)
	Additional equipment Power reduction, control phase (LR) Power reduction, self-sufficient (LRA) Constant Light Output (CLO)
	Accessories Shieldings Release bracket Junction boxes Post mounting elements Reduction pieces Wall mountings



CONTACTS

TRILUX GmbH & Co. KG

Heidestrase • D-59759 Arnsberg

Postfach 19 60 • D-59753 Arnsberg

GERMANY

Tel. +49 2932 301-0

www.trilux.com/en

SiSEL Mühendislik Elektronik San. ve Tic. A.Ş.

Şerifali Mah. Barbaros Cad. No 18

34775 Ümraniye İstanbul

TURKEY

Tel: +90 (216) 499 46 64

www.endalight.com

All technical data including dimensional and weight specifications have been compiled with due care. Errors reserved. Possible colour deviations are due to printing processes. We reserve the right to modify in the interest of progress. Luminaires are partly shown with accessories that must be ordered separately. Images of installations may show custom-manufactured luminaires. This publication was printed on PEFC-certified paper in an environmentally friendly way.